

EXC Wire & Cable™

Cat5e UTP Outdoor Ethernet Cable

The outdoor Cat5e cable is an enhanced twisted pair that is suitable for higher network transfer rates, such as 100Mbps or 1Gbps. This network cable is suitable for outdoor environments, with high tensile strength and protection. It is composed of multiple pairs of twisted pairs and a plastic shell, can provide good network transmission performance, and can resist various environmental factors, such as wind and rain, high temperature, low temperature and so on.

Features & Benefits

- · Suitable for Gigabit Ethernet applications
- · PE outer sheath
- Supplied metre marked in easy pull boxes for easy installation
- Pure copper cores
- Excellent performance exceeding ANSI/TIA enhanced Category 5 specifications

Product Specifications				
Inner Conductor	24 AWG plain copper			
Insulation	High density polyethylene			
Construction	4 twisted pairs cabled together			
Colour Code	Pair 1: White/Blue-Blue/White Pair 2: White/Orange-Orange/White Pair 3: White/Green-Green/White Pair 4: White/Brown-Brown/White			
Sheath	PE external (Black)			
Colour	Black			
Overall Diameter	5.2mm +/- 0.3 mm			
Min. Bending Radius	20 mm			
Impedance	100MHz +/- 15 Ω			
Conforms to	ANSI/TIA-568-C, ISO11801, Cenelec EN50173			
Length Available (metres)	305m			



Diagram	

- 1. Outer Sheath PE
- High Density Polyethylene Instillation
- 3. Copper Core
- 4. Rip Cord5. HDPE Insulation

Electrical Specifications					
DC Resistance Unbalance	Max 2.5				
Insulation Resistance			>5	5000mΩ*km	
Characteristic Impedance @1-250 MHz			100 ľ	MHz +/- 15 Ω	
Velocity Ratio				69%	
Operating Temperature Range	-20°C to +70°C				
Installation Temperature Range	0°C to +50°C				
Transfer Impedance (mΩ/m)	1 MHz	10 MHz	30 MHz	1 00MHz	

